

Spannköpfe ohne Vorbau

Grösse	Länge	Art	Schritt in mm	Profil	Spannfläche	Spanndurchmesser	Referenz Bestell-Nr.	
32	44	kurze Version	1	●	glatt	3.0–32.0	32RDL 03 - 32	
					quergerillt	8.0–32.0	32RDR 08 - 32	
					längs- und quergerillt	11.0–32.0	32RDS 11 - 32	
				⬡	glatt	7.0–27.0	32RHL 07 - 27	
					quergerillt	8.0–27.0	32RHR 08 - 27	
					glatt	7.0–22.0	32RCL 08 - 22	
			■	quergerillt	8.0–22.0	32RCR 08 - 22		
				0.5	●	glatt	3.0–42.0	42RDL 03 - 42
						quergerillt	8.0–42.0	42RDR 08 - 42
längs- und quergerillt	11.0–42.0		42RDS 11 - 42					
⬡	glatt		7.0–38.0		42RHL 07 - 38			
	quergerillt		8.0–38.0		42RHR 08 - 38			
	glatt		7.0–28.0		42RCL 07 - 28			
■	quergerillt		8.0–28.0	42RCR 08 - 28				
	0.5		●	glatt	3.0–52.0	52RDL 03 - 52		
					7.0–45.0	52RHL 07 - 45		
7.0–36.0					52RCL 07 - 36			
1			⬡		glatt	4.0–65.0	65RDL 04 - 65	
		quergerillt			8.0–65.0	65RDR 08 - 65		
		längs- und quergerillt			11.0–65.0	65RDS 11 - 65		
1	⬡	glatt	7.0–56.0	65RHL 07 - 56				
		quergerillt	8.0–56.0	65RHR 08 - 56				
		glatt	7.0–46.0	65RCL 07 - 46				
	■	quergerillt	8.0–46.0	65RCR 08 - 46				
		1	●	glatt	5.0–80.0	80RDL 05 - 80		
					7.0–68.0	80RHL 07 - 68		
7.0–56.0	80RCL 07 - 56							

Spannköpfe mit Vorbau

Grösse	Länge	Art	Schritt in mm	Profil	Spannfläche	Spanndurchmesser	Referenz Bestell-Nr.	
42	47	lange Version	0.5	●	glatt	3.0–7.5	42VRDL 03 - 07	
					quergerillt	8.0–10.5	42VRDR 08 - 10	
					längs- und quergerillt	11.0–42.0	42VRDS 11 - 42	
				⬡	glatt	7.0–38.0	42VRHL 07 - 38	
					quergerillt	8.0–38.0	42VRHR 08 - 38	
					glatt	7.0–28.0	42VRCL 07 - 28	
			■	quergerillt	8.0–28.0	42VRCR 08 - 28		
				1	●	glatt	3.0–52.0	52RDL 03 - 52
						quergerillt	8.0–52.0	52RDR 08 - 52
längs- und quergerillt	11.0–52.0		52RDS 11 - 52					
⬡	glatt		7.0–45.0		52RHL 07 - 45			
	quergerillt		8.0–45.0		52RHR 08 - 45			
	glatt		7.0–36.0		52RCL 07 - 36			
■	quergerillt		8.0–36.0	52RCR 08 - 36				
	0.5		●	glatt	4.0–7.5	65VRDL 04 - 07		
					8.0–10.5	65VRDR 08 - 10		
11.0–65.0					65VRDS 11 - 65			
1			⬡		glatt	7.0–56.0	65VRHL 07 - 56	
		quergerillt			8.0–56.0	65VRHR 08 - 56		
		glatt			7.0–46.0	65VRCL 07 - 46		
■	quergerillt	8.0–46.0	65VRCR 08 - 46					
	1	●	glatt	5.0–80.0	80RDL 05 - 80			
				8.0–80.0	80RDR 08 - 80			
11.0–80.0				80RDS 11 - 80				
⬡		glatt		7.0–68.0	80RHL 07 - 68			
		quergerillt		8.0–68.0	80RHR 08 - 68			
		glatt		7.0–56.0	80RCL 07 - 56			
■	quergerillt	8.0–56.0	80RCR 08 - 56					

Synchro-SZ / Segmentspannkopf

für INDEX 36/42/52/60 ABC

Grösse	Länge	Kopfdurchmesser	Schritt in mm	Profil	Spannfläche	Spanndurchmesser	Referenz Bestell-Nr.
421	39	59.6	0.5	●	glatt	4.0–42.0	421RDL 04 - 42
			1	⬡		7.0–36.0	421RHL 07 - 36
				■		7.0–29.0	421RCL 07 - 29

Spannköpfe weich ausdrehbar

Grösse	Länge	Art	Profil	Spannfläche	Spanndurchmesser	Referenz Bestell-Nr.			
32	44	Stirnfläche und Bohrung weich	●	glatt	5.0	32RDW 5			
					10.0	32RDW 10			
					20.0	32RDW 20			
42	42				●	5.0	42RDW 5		
						15.0	42RDW 15		
						30.0	42RDW 30		
52	46		●			5.0	52RDW 5		
						15.0	52RDW15		
						30.0	52RDW 30		
65	53				●	5.0	65RDW 5		
						10.0	65RDW 10		
						20.0	65RDW 20		
			40.0			65RDW 40			
			80			53	●	8.0	80RDW 8
								20.0	80RDW 20
40.0	80RDW 40								
60.0	80RDW 60								